



SQUAREPLUG™ SP400/400BK<sup>(1)</sup>, SP500/500BK<sup>(1)</sup>, SP550-S/550-SBK<sup>(1)</sup>, SPS4/4BK<sup>(2)</sup> and SPS5/5BK<sup>(2)</sup> ARE PROPRIETARY DESIGNS OF KMMK SOLUTIONS.

<sup>(1)</sup>EU PATENT No. 003074582-000 | <sup>(1)</sup>US PATENT No. D808.838 | <sup>(2)</sup>EU PATENT No. 004063857-0001/0002 | <sup>(2)</sup>US PATENT PENDING  
WWW.KMMK.SOLUTIONS

SPECS AND FEATURES	SP400 – SP400BK	SP500 – SP500BK	SP550-S – SP550-SBK	SPS4 – SPS4BK	SPS5 – SPS5BK
DESIGNATION	SUPER LOW PROFILE ANGLED 1/4" TS [MONO] CONNECTOR	SUPER LOW PROFILE ANGLED 1/4" TS [MONO] CONNECTOR	SUPER LOW PROFILE ANGLED 1/4" TRS [STEREO] CONNECTOR	SHORT BODY STRAIGHT 1/4" TS [MONO] CONNECTOR	SHORT BODY STRAIGHT 1/4" TS [MONO] CONNECTOR
THICKNESS	0.326" [8.3mm]	0.326" [8.3mm]	0.350" [8.9mm]		
WIDTH	0.67" [17mm]	0.67" [17mm]	0.67" [17mm]		
HEIGHT	1.10" [28mm]	1.10" [28mm]	1.10" [28mm]		
DIAMETER				0.51" [13mm]	0.51" [13mm]
LENGTH				0.787" [20mm]	0.787" [20mm]
STRAIN RELIEF	✓	✓	✓	✓	✓
COLOR CODING	✓	✓	✓	✓	✓
FINISH	SP400: SILVER   SP400BK: BLACK [BODY + COVER + SCREWS]	SP500: SILVER   SP500BK: BLACK [BODY + COVER + SCREWS]	SP550-S: SILVER   SP550-SBK: BLACK [BODY + COVER + SCREWS]	SPS4: SILVER   SPS4BK: BLACK [HANDLE + SCREWS]	SPS4: SILVER   SPS4BK: BLACK [HANDLE + SCREWS]
FITS CABLES UP TO	0.18" [4.6mm] OD	0.22" [5.6mm] OD	0.25" [6.2mm] OD	0.19" [4.8mm] OD	0.23" [5.8mm] OD
SNUG-FIT CABLES OF ABOUT	0.18" [4.6mm] OD	0.22" [5.6mm] OD	0.25" [6.2mm] OD	0.19" [4.8mm] OD	0.23" [5.8mm] OD
2 SOLDER TABS	✓	✓		✓	✓
3 SOLDER TABS			✓		
INSULATION SHEET	✓	✓	✓		
INSULATION TUBE				✓	✓



## CABLES COMPATIBILITY CHART

- TIGHT OR CLOSE-TO-TIGHT FIT
- FIT
- NO FIT

BRAND / MODEL	OD CAPACITANCE	SP400 – SP400BK	SP500 – SP500BK	SP550-S – SP550-SBK	SPS4 – SPS4BK	SPS5 – SPS5BK
BELDEN 1865A	0.155" [4mm] 16pF/ft. [53pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
BELDEN 8218	0.155" [4mm] 20pF/ft. [65pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
BTPA CA 0492	0.150" (3.8mm) 37pF/ft. [121pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
BTPA CA 0678	0.178" [4.5mm] 20pF/ft. [65pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
B LAWRENCE 150	0.155" [4mm] 20pF/ft. [65pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CANARE GS4	0.157" [4mm] 47pF/ft. [155pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CANARE GS6	0.228" [5.8mm] 49pF/ft. [160pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
EVIDENCE MONORAIL	0.155" [4mm] 23pF/ft. [75pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
FREE THE TONE 416	0.155" [4mm] 49pF/ft. [160pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
GEORGE L'S 155	0.155" [4mm] 20pF/ft. [65pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
GEORGE L'S 255	0.225" [5.7mm] 20pF/ft. [65pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
LAVA MINI ELC	0.195" [5mm] 31pF/ft. [101pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
LAVA MINI TIGHTROPE	0.195" [5mm] 32pF/ft. [105pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
LAVA MINI ULTRAMAFIC	0.195" [5mm] 30pF/ft. [98pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
MOGAMI 2314	0.155" [4mm] 33pF/ft. [110pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
MOGAMI 2319	0.197" [5mm] 47pF/ft. [155pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
MOGAMI 2524	0.23" [6mm] 39pF/ft. [130pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
MOGAMI 2552	0.197" [5mm] 27pF/ft. [97pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
REDCO TGS-MD	0.195" [5mm] 44pF/ft. [150pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SOMMER SC-ONYX TYNEE	0.155" [4mm] 38pF/ft. [125pF/m]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SOMMER TRI CONE	0.23" [5.9mm]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

MKII	26pF/ft. [85pf/m]					
SOMMER TRI CONE XXL	0.23" [5.9mm] 26pF/ft. [85pf/m]	✘	✘	☑	✘	☑
VAN DAMME FC90	0.23" [5.9mm] 27pF/ft. [90pf/m]	✘	✘	☑	✘	☑
VAN DAMME PRO PATCH	0.19" [4.9mm] 29pF/ft. [95pf/m]	✘	☑	✓	✘	☑
VAN DAMME SILVER HC125	0.23" [5.9mm] 38pF/ft. [125pf/m]	✘	✘	☑	✘	☑

#### SWITCHERS COMPATIBILITY CHART

✓ COMPATIBLE [PLUGS CAN FIT SIDE BY SIDE]

✘ NOT COMPATIBLE [PLUGS CANNOT BE PLUGGED NEXT TO ONE ANOTHER]

BRAND	MODEL	SP400 – SP400BK	SP500 – SP500BK	SP550-S – SP550-SBK	SPS4 – SPS4BK	SPS5 – SPS5BK
BOSS	ES5   ES8	✘	✘	✘	✓	✓
DISASTER AREA	DPC5   DPC8EZ	✓	✓	✓	✓	✓
CARL MARTIN	OCTASWITCH   OCTASWITCH MKII	✓	✓	✓	✓	✓
CUSACK MUSIC	PBT6, PBT9	✓	✓	✓	✓	✓
G-LAB	GSC2   GCS3	✓	✓	✓	✓	✓
IDEA BENCH	SWITCHER00	✓	✓	✓	✓	✓
LEHLE	PARALLEL L   LITTLE DUAL   DUAL SGOS   D LOOP SGOS   1AT3 SGOS   3AT1 SGOS   P-SPLIT II	✓	✓	✓	✓	✓
MUSICOM LAB	EFX 6M   62M   8L   MKIV   MKV   LE	✓	✓	✓	✓	✓
ONE CONTROL	OC10	✓	✓	✓	✓	✓
PROVIDENCE AUDIO	PEC4V   PEC2	✓	✓	✓	✓	✓
RJM MUSIC	PBC10   MINI EFFECT GIZMO	✓	✓	✓	✓	✓
THE GIG RIG	QUARTER MASTER QMX2   4   6   8   10	✓	✓	✓	✓	✓
THE GIG RIG	G2	✘	✘	✘	✓	✓
VINTECK	V8	✓	✓	✓	✓	✓
VOODOOLAB	PEDAL SWITCHER, PX8, PX8 PLUS	✓	✓	✓	✓	✓
VOODOOLAB	HEX	✘	✘	✘	✓	✓
WALRUS AUDIO	TRANSIT 5	✓	✓	✓	✓	✓